

Huawei Embedded Power System



Embedded DC Power System

ETP4890-A2

Introduction

ETP4890-A2 embedded DC power system can convert from AC input to stabilized -48V DC output. It can be compatible with 15A and 30A rectifiers and provide 90A output with 2U in height. ETP4890-A2 can be embedded in 19-inch rack or cabinet or other scenarios. The system can provide excellent performance such as intelligent battery management, remote management, etc.

Features

- Wide range of AC input voltage from 85V to 300V
- Wide operation temperature range of rectifier from -40°C to 75°C
- Online-swappable rectifier provides easy installation and maintenance
- Standard installation structure design, adapting to various scenarios
- Compact design, saving space and installation cost
- High rectifier efficiency over 96% helps to save energy
- Excellent rectifier dormancy function helps to increase system efficiency
- Intelligent battery management and protection helps to prolong battery lifespan
- Support environment monitoring and remote management through dry contact, serial interface or Ethernet interface

Application Scenarios

- Access network
- Transmission network
- Communication network of enterprise



ETP4890-A2



15A rectifier



30A rectifier



Monitoring unit
SMU01C

Specifications

Product		ETP4890-A2		
System	Dimension	442mm(W)×255mm(D)×86.1mm(2U,H)		
	Weight	≤10kg(fully loaded)		
	Cooling mode	Natural cooling		
	Installation mode	Installed on 19-inch rack or cabinet		
	Cabling mode	Front inlet and front outlet		
	Maintenance mode	Front access, support module grade alteration		
	Protection level	IP20		
AC Distribution	Input mode	220/380VAC 3-phase or 220VAC Single phase or 110VAC dual-live wire		
	Input frequency	45~66Hz, rated value: 50Hz/60Hz		
	SPD	5kA/10kA, 8/20μs		
DC Distribution	Output voltage	42~58VDC, rated value: 53.5VDC		
	Maximum capacity	4.8kW		
	Battery breakers	1×80A		
	Load breakers	1×10A, 1×30A, 2×40A		
Environment	Operating temperature	-40°C~+65°C		
	Storage temperature	-40°C~+70°C		
	Operating humidity	5%~95%(non-condensing)		
	Altitude	0~4000m (If the altitude is within the range of 2000m to 4000m, the maximum operating temperature decreases by 1°C as the altitude increases by 200m.)		
Rectifier	Rated power	870W (176~300VAC)	1000W (176~300VAC)	1600W (176~300VAC)
	Input voltage	85VAC~300 VAC, rated 220VAC		
	Working temperature	-40°C~+75°C (derated output above 65°C)	-40°C~+75°C (derated output above 55°C)	-40°C~+75°C (derated output above 55°C)
	Dimension	95.5mm(W)×208mm(D)×40.8mm(H)		
	Weight	≤1.5kg	≤1.1kg	<1.6kg
	Cooling mode	Forced cooling		
	Power factor	≥0.99		
	THD	≤5%		
Controller	Type	SMU01C		
	Signal input	2 digital input		
	Alarm output	4 dry contact		
	Communication port	RS232/485		
	Display mode	LCD		

Remark: Optional rectifiers with power efficiency >92% are available for this system.

Copyright © Huawei Technologies Co., Ltd. 2014. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademark Notice

 , HUAWEI, and  are trademarks or registered trademarks of Huawei Technologies Co., Ltd.
Other trademarks, product, service and company names mentioned are the property of their respective owners.

General Disclaimer

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.

HUAWEI TECHNOLOGIES CO., LTD.

Huawei Industrial Base
Bantian Longgang
Shenzhen 518129, P.R. China
Tel: +86-755-28780808
Version No.: M3-035746-20140506-C-2.0

www.huawei.com